



### APPLICATION

Draft systems serving all gas, liquid, and solid fuel burning appliances.

### LISTINGS & RATINGS

UL 378—Standard for draft equipment, up to 1000°F continuous, 1400°F abnormal

### FUNCTION

Improves the efficiency of solid, liquid, and gas burning appliances by creating steady draft

### DESCRIPTION

KW Barometric Draft Regulators, also known as Barometric Dampers, help maintain constant and efficient fuel consumption in solid, liquid, or gas burning heating appliances. Barometric Draft Regulators compensate for changes in temperature, wind, pressure, as well as seasonal weather changes by limiting the negative pressure in the system to maintain a steady and consistent draft.

### CONSTRUCTION

- 304L Stainless Steel
- Includes brass control wheel; does not require additional balancing weights
- Integrated relief mechanism for gas appliances

Model	ZUK 130	ZUK 150	ZUK 150-S	ZUK 180
max. flue gas temperature (DIN 1860)	750 °F	750 °F	750 °F	750 °F
Setting range (required draft in neg. pressure)	0.04–0.10"	0.04–0.14"	0.04–0.14"	0.04–0.24"
Air flow rate at $\Delta p$ 0.02" wc	45 CFM	80 CFM	80 CFM	110 CFM
Airflow rate at $\Delta p$ 0.08" wc	75 CFM	130 CFM	130 CFM	160 CFM
Airflow rate at $\Delta p$ 0.16" wc	95 CFM	175 CFM	175 CFM	210 CFM
Response pressure of pressure relief valve	> 0.40" wc	> 0.40" wc	-----	> 0.40" wc
max. open cross-section pr. relief valve	10 in <sup>2</sup>	5.25 in <sup>2</sup>	-----	5.25 in <sup>2</sup>
Air flow rate as combined sec.-air appliance at $\Delta p$ 0.08" wc	> 60 CFM	-----	> 130 CFM	> 120 CFM

The air flow rates given for  $\Delta p$  refer to the negative static pressure above the set point of the barometric damper.

### Kutzner + Weber USA

Distributed by RM Manifold Group, Inc

120 S. Sylvania Avenue, Suite A • Fort Worth, TX 76111

Phone: (817) 393-4029

[www.kw-usa.com](http://www.kw-usa.com)

[www.rmmanifold.com](http://www.rmmanifold.com)



Intertek