

KW

KUTZNER + WEBER



Fireplace
Exhaust
Solutions

RSD Fans

The RSD high temperature exhaust fan from KW maintains the required negative pressure for gas and wood burning fireplaces up to 2,100 CFM.



Model Number	RSD150	RSD250	RSD350
Capacity	450 CFM	900 CFM	2,100 CFM
Pressure	.50" wc static	.75" wc static	1.0" wc static
Material	316L Stainless Steel	316L Stainless Steel	316L Stainless Steel

Constructed of 316L stainless steel to prevent corrosion and is UL listed up to 1000°F continuous.



The tool-less clamp and hinge provides easy access to the impeller for routine maintenance and cleaning.

Accessories

The RSD fan can be combined with a number of accessories to provide the right system for your fireplace.



Keyfob Remote



Control with Alarm



Automatic Flue Damper



Automated Fan Control

Packages

Standard

Includes fan, adapter and FSC100 fan speed control

A simple solution to ensure proper draft for your fireplace



Standard Plus

Includes fan, adapter and FSC200 fan controller with alarm and airflow switch for gas fireplaces

Add a visual and audible alarm function to your Standard package plus an optional mechanical damper



Premium

Includes fan, adapter and FSC300 automatic fan controller with alarm and pressure transducer

Includes a fully automated fan speed controller with an alarm and pressure sensor for best performance in your fireplace, plus an optional automatic damper



Options

Automatic Flue Damper

Add an automatic flue damper to your Premium or Plus Package for a completely integrated system



(817) 393-4029
www.kw-usa.com

DISTRIBUTED BY:

RM Manifold Group, Inc
120 S Sylvania Ave, Suite A
Fort Worth, TX 76111

KW

KUTZNER + WEBER

KW

KUTZNER + WEBER

